

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 October 2004 (07.10.2004)

PCT

(10) International Publication Number
WO 2004/084777 A2

(51) International Patent Classification⁷: A61F 5/44

(21) International Application Number:
PCT/DK2004/000211

(22) International Filing Date: 26 March 2004 (26.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 2003 00471 27 March 2003 (27.03.2003) DK

(71) Applicant (for all designated States except US): COLO-
PLAST A/S [DK/DK]; Høltedam 1, DK-3050 Humlebaek
(DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CIOK, Danuta

[PL/DK]; Violens Kvarter 8, DK-2990 Nivaa (DK).
STROEBECH, Esben [DK/DK]; Selmersvej 11,
DK-2970 Hoersholm (DK).


(74) Common Representative: COLOPLAST A/S; Høltedam
1, DK-3050 Humlebaek (DK).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: AN OSTOMY APPLIANCE



(57) Abstract: An ostomy appliance comprising a front wall and a rear wall of flexible material forming a bag, said rear wall having an opening for receiving a stoma, and said rear wall also being provided with an adhesive wafer for securing the appliance to a user's skin, said wafer having a hole being aligned with the opening for receiving the stoma, wherein the opening has an edge being secured to the surface of the adhesive wafer facing away from the user in an attachment zone surrounding the hole of the wafer, wherein a first part of the edge of the opening of the bag is secured to the surface of the wafer in a corresponding first part of the attachment zone, and wherein a second, remaining part of the edge of the opening of the bag is prepared for adhesive sealing of the same to the remaining second part of the attachment zone renders it possible for a nurse to observe the stoma area during adaptation of such a sealing member when applying one-piece appliances.

WO 2004/084777 A2

TITLE

An Ostomy Appliance

BACKGROUND OF THE INVENTION**5 1. Field of the Invention**

The present invention relates to an ostomy appliance and to a method of applying an ostomy appliance body side member around a stoma.

10 In connection with surgery for a number of diseases in the gastro-intestinal or urinary tract a consequence is, in many cases, that the colon, the ileum or the ureter has been exposed surgically and the patient is left with an abdominal stoma, or, in nephrostomy or ureterostomy, the ureter or a catheter is exposed in the back or the chest region or abdominal region, and the effluents or waste products of the body, which are conveyed through these organs, are discharged
15 through the artificial orifice or opening and are collected in a collection bag, which is usually adhered to the skin by means of an adhesive wafer or plate having an inlet opening for accommodating the stoma/ureter/catheter. Also in connection with a fistula, the patient will have to rely on an appliance to collect the bodily material emerging from such opening.

20

Ostomy appliances are well known. Such appliances may be two-piece or one-piece appliances. In both types of appliances, an adhesive barrier member (or base plate) is attached to the wearer's abdomen/back/chest. In case of a one-piece appliance, a receiving member or bag is permanently attached to the base
25 plate. In case of a two-piece appliance, the adhesive barrier member forms part of a body side member and a receiving member or bag is attached releasably to the body side ostomy member for receiving exudates from the stoma.

30 When using one-piece appliances, the whole appliance, including the adhesive skin barrier securing the appliance to the skin is normally removed and replaced by a fresh appliance. When using two-piece appliances, the body side ostomy member is left in place up to several days, and only the receiving member or bag

attached to the body side member is replaced. The attachment means for attaching an ostomy receiving bag may e.g. be a system known per se comprising matching coupling rings or matching flanges and adhesive surfaces engaging with and sealing against a flange area of the body side member.

5

It is necessary to change the body side member of a two-piece appliance when the centre part of the adhesive wafer has been sufficiently deteriorated to allow access of the aggressive exudates to the skin surrounding the stoma, irrespective of the fact that the wafer as such has a much longer wearing time. The access of aggressive exudates to the skin is causing skin problems.

10

Frequent changing of the body side member of a two-piece appliance is undesirable due to the irritation of the skin and the quality of life of the user may be improved and the nuisance of the wearing of an ostomy appliance reduced if the intervals between exchanging of body side member can be increased.

15

The service time of the body side ostomy member depends *inter alia* of the amount and the aggressiveness of the exudates and of the sealing between the stoma and the body side ostomy member.

20

The sealing depends on the fit to the stoma. Conventionally, only a limited number of standard appliances having holes of different size are available and the user or an assistant must customise the body side member by cutting the edge of the hole to adapt the body side member to the stoma.

25

2. Description of the Related Art

When cutting the edge of the hole of an adhesive wafer of a conventional one-piece ostomy appliance for adapting the same to the size and shape of a stoma the cutting is complicated by the fact that in order to secure discretion, for decorative purposes and for providing softness, low noise generation and comfort the bag is often made from an opaque material or covered and/or provided with a cover or front layer rendering it very difficult, if not impossible for the user or the

30

nurse to observe the stoma area during determination of a cutting line for adaptation of the hole or when applying the appliance.

Published International Patent Applications Nos. WO 98/17212 and WO
5 98/53771 disclose ostomy appliances comprising a body side member
comprising an adhesive wafer for securing the appliance to the user's skin, said
wafer having a hole for receiving a stoma, and an optionally separately
exchangeable receiving member or bag secured to the body side ostomy
member for receiving secretions from the ostomy said ostomy appliance further
10 comprising a sealing member disposed in the hole of the wafer surrounding the
stoma and having a hole for accommodating the stoma.

The ostomy appliance disclosed in Published International Patent Application No.
WO 98/53771 has a sealing member having balanced plastic and elastic
15 properties allowing a better adaptation of the hole of the ostomy appliance to a
stoma by a temporary enlarging of the hole by everting or rolling up the inner rim
of the hole for accommodating the stoma.

WO 98/17212 and WO 98/53771 only teach the use of such a sealing member
20 together with two-piece ostomy appliances and do neither disclose nor indicate
how to use a sealing member together with one-piece ostomy devices.

It has been found desirable in practice to make use of separate sealing members
for facilitating the adaptation of an ostomy appliance and the sealing between the
25 ostomy appliance and the stoma.

If used with a one-piece ostomy appliance, such a sealing member would be
difficult to manipulate for several reasons.

30 Firstly, it is very difficult to adapt the sealing member to the stoma after applying
the ostomy appliance if the sealing member has a tacky surface on the side
facing the bag as it will then adhere to the bag during attempts to adapt the

sealing member to the stoma which must be performed by pressing the wall of the bag against the sealing member. Then, also a risk exists that the wall of the bag is torn when trying to disengage the contact.

- 5 Secondly, due to the measures to secure discretion, for decorative purposes and for providing softness, low noise generation and comfort stated above it also in this case very difficult, if not impossible for the user or the nurse to observe the stoma area during adaptation of such a sealing member when applying one-piece appliances.

10

SUMMARY OF THE INVENTION

- The invention relates to an ostomy appliance comprising a front wall and a rear wall of flexible material forming a bag, said rear wall having an opening for receiving a stoma, and being provided with an adhesive wafer for securing the appliance to a user's skin, said wafer having a hole being aligned with the opening for receiving the stoma, wherein the opening of the rear wall has an edge being adapted to be secured to a surface of the adhesive wafer facing away from the user in an attachment zone surrounding the hole of the wafer, and wherein a first part of the edge of the opening of the rear wall is permanently secured to the surface of the wafer in a corresponding first part of the attachment zone, and a second, remaining part of the edge of the opening of the bag is prepared for adhesive sealing of the same to the remaining second part of the attachment zone.

- 25 Furthermore, the invention relates to a method of applying to the abdomen an ostomy appliance comprising a front wall and a rear wall of flexible material forming a bag, said rear wall having an opening for receiving a stoma, and said rear wall also being provided with an adhesive wafer for securing the appliance to a user's skin, said wafer having a hole being aligned with the opening for receiving the stoma, wherein the opening has an edge being secured to the surface of the adhesive wafer facing away from the user in an attachment zone surrounding the hole of the wafer.

30

Still further, the invention relates to a method of applying an ostomy appliance comprising a front wall and a rear wall of flexible material forming a bag, said rear wall having an opening for receiving a stoma, and said rear wall also being
5 provided with an adhesive wafer for securing the appliance to a user's skin, said wafer having a hole being aligned with the opening for receiving the stoma, said hole comprising a sealing member having a second hole for receiving a stoma, wherein the opening has an edge being secured to the surface of the adhesive
10 wafer facing away from the user in an attachment zone surrounding the hole of the wafer.

Brief Description of the Drawings

The invention is disclosed more in detail with reference to the drawings in which Fig. 1 shows an ostomy appliance of the invention in its open state,
15 Fig. 2 shows another embodiment of an ostomy appliance of the invention in its open state applied to a users abdomen,
Fig. 3 shows further embodiment of an ostomy appliance of the invention in its closed state, and
Fig. 4 shows a stiffening element for use in an ostomy appliance of the invention.
20

Detailed Description of the Present Invention

According to a FIRST ASPECT the present invention relates to an ostomy appliance comprising a front wall and a rear wall of flexible material forming a bag, said rear wall having an opening for receiving a stoma, and being provided
25 with an adhesive wafer for securing the appliance to a user's skin, said wafer having a hole being aligned with the opening for receiving the stoma, wherein the opening of the rear wall has an edge being adapted to be secured to a surface of the adhesive wafer facing away from the user in an attachment zone surrounding the hole of the wafer, and wherein a first part of the edge of the opening of the
30 rear wall is permanently secured to the surface of the wafer in a corresponding first part of the attachment zone, and a second, remaining part of the edge of the

opening of the bag is prepared for adhesive sealing of the same to the remaining second part of the attachment zone.

5 As a part of the edge of the bag of a one-piece appliance is not secured to the adhesive wafer, that part of the edge may be folded back giving access to the stoma area from the distal side of the appliance facing away from the user during the application of the appliance. Thus, a simple evaluation of the stoma area for cutting the wafer for adapting the same to the specific stoma and manipulation and location of an adhesive wafer in relation to the stoma is enabled. All such
10 adaptation and application may be carried out having full view over the stoma area from the distal side. Then, the edge of the bag is easily sealed to the wafer along the remaining part of the attachment zone, and thus along the full periphery of the bag, using an adhesive. The adhesive is preferably protected by a release liner until the final sealing of the bag. The bag is preferably sealed permanently to
15 the wafer. Thus, in use, after application the product works like a conventional one-piece appliance, and advantages of access to the stoma area when working with two-piece appliances are transferred to the one-piece technology.

20 The opening of the rear wall has an edge which is adapted to be secured to a surface of the adhesive wafer. Such securing may be achieved by attachment of the edge e.g. by means of an adhesive. In some embodiments only the edge of the rear wall is adapted to be secured to the surface of the adhesive wafer while in other embodiments also an area adjacent to the edge may be secured or attached to the surface of the adhesive wafer.

25

A release liner may be provided on the second remaining part of the edge of the opening of the rear wall. In order to adhere the second remaining part of the rear wall to the wafer the release liner must be removed.

30 In one embodiment the second, remaining part of the edge of the opening of the rear wall is adapted to be changed from a first position wherein is in not adhesively sealed to the remaining second part of the attachment zone, and a

second position wherein it is adhesively sealed to the remaining second part of the attachment zone.

5 In an embodiment the second, remaining part of the edge of the opening of the bag is prepared for permanently adhesive sealing of the same to the remaining second part of the attachment zone. Thus in the latter embodiment when the second remaining part has been permanently adhered to the second part of the attachment zone it may be difficult or even impossible to remove it again. Accordingly if one succeeds in removing the second part it can not be re-attached
10 again.

The resulting hole may however show an exposed edge which does not provide a sufficient sealing against a stoma ensuring that no leak occurs and may injure the surface of the stoma e.g. when the user bends or turns due to the exposed
15 edge of the carrier sheet which after cutting even may show a serrated edge.

In one embodiment the ostomy appliance is in the form of a set which comprises a separate sealing member for disposing in the hole of the wafer surrounding the stoma and having a hole for accommodating the stoma. The present invention
20 enables the use of such a sealing member together with one-piece ostomy appliances and enables an easy manipulation and shaping of such sealing member before application and to seal between the adhesive wafer and the stoma avoiding direct contact between the stoma and the edge of the hole. Thus, the edge of the hole of the sealing member may be everted or rolled and the
25 sealing member positioned from the distal side of the appliance or from "inside the bag".

The use of a separate sealing member also enables a reduction in the number of available sizes of holes as one or a few large sizes of holes may be tailored to
30 most stomas using the separate sealing member, which has not been possible for one-piece ostomy appliances until now. Furthermore, the cutting for enlarging

the hole of a one-piece ostomy appliance for accommodating a stoma is rendered easier as the fit is not critical.

5 In accordance with a suitable embodiment of the invention, the second part of the edge of the bag is secured to one surface of a stiffening element reducing the risk of wrinkling of the edge of the bag.

10 When the first and the second part of the edge of the bag are secured to a first and a second part, respectively, of one surface of the stiffening element, the handling of the bag and the securing of the first part of the edge of the bag to the first part of the attachment zone are facilitated and the process is readily adapted for automatic production.

15 A stiffening element is preferably in the form of a ring being secured to the circumference of the opening of the bag. Such stiffening element may suitably be made from a plastics material, which is flexible and relatively rigid so that it is substantially dimensionally stable under normally occurring loads. Polyolefins, particularly polyethylene, e.g. in the form of a blend of high and low density polyethylenes, have been found suitable, but other materials having similar
20 properties may be used. The stiffening element may alternatively be in the form of a flange of a foam material such as a cellular plastic material conventionally used for production of flanges for ostomy appliances. A polyurethane foam is suitably used.

25 The adhesive for adhesive sealing of the second part of the edge of the bag or the stiffening element to the second part of the attachment zone is suitably an "aggressive" adhesive material providing an immediate grip when contacted with the other surface after removing a release liner. It is preferred that the adhesive material has a sufficient thickness and is sufficiently mouldable to provide a
30 reliable sealing of the edge of the bag. A suitable adhesive material is pressure sensitive adhesive suitable for use with the parts to be united such as acrylic adhesives, elastomeric adhesives, polyurethane adhesives, or polyester

adhesives. The choice of adhesive may be made in accordance with the above requirements, as it is not critical for the invention in the respect that the adhesive is not in contact with the skin. It is also contemplated that the adhesive properties of the adhesive and the second part of the edge of the bag or the stiffening
 5 element and the second part of the attachment zone are balanced enabling an opening and resealing of the bag, if desired.

It is suitable when the stiffening element is a flat ring provided with two notches dividing the flat ring into two parts. The shape of such ring should correspond to
 10 the shape of the attachment zone and may e.g. be circular or elliptical. Such notches provide predetermined zones in which the stiffening element is readily folded back giving access to the distal side of the adhesive wafer. The notches may be present on the proximal surface of the stiffening element or on the distal surface of the stiffening element whichever deemed most appropriate. When
 15 placed on the distal surface of the stiffening element, care must be taken when securing the edge of the bag to the stiffening element that the edge of the bag is reliably sealed to the surface without canals in the notch-area. The securing may e.g. be effected by welding or suitably applying an adhesive, preferably in an amount ensuring a reliable sealing in the notch-area. A combination of a welding
 20 seam and adhesive sealing may be used if deemed appropriate.

It is especially suitable to locate the notches stretch essentially along a chord of the circular ring facilitating the bending of the stiffening element. The notches stretch essentially along a diameter of the circular ring giving a large opening to
 25 the stoma site in the ostomy appliance.

In one embodiment of the invention the part of the stiffening element secured the second part of the bag is provided with an adhesive layer being covered by a protecting layer. In case that the notches are located on the proximal surface of
 30 the stiffening element, care must be taken to ensure that the notch is sealed reliably when adhering the second of the edge of the bag to the second part of

the attachment zone, e.g. by applying a sufficient amount of adhesive material to fill the notch.

5 A stiffening element to be used in accordance with the present invention may be made by a method known per se for manufacturing products from the selected materials such as injection moulding, die casting, pressing, or foaming using corresponding moulds. Alternatively, a stiffening element may be cut from a work-
10 piece of the desired material such as a foam block. A notch may be prepared when forming the stiffening element or later using methods known per se such as cutting or milling.

In another embodiment of the invention the second part of the attachment zone of the wafer is provided with an adhesive layer being covered by a protecting
15 layer. In case that the notches are located on the proximal surface of the stiffening element, care must also be taken in this case to ensure that the notch is sealed reliably when adhering the second of the edge of the bag to the second part of the attachment zone, e.g. by applying a sufficient amount of adhesive material at the site of the attachment zone near the notch to fill the notch.

20 In a further embodiment of the invention, the front wall is provided with an opening provided with cover, which may be released and resealed and thus giving temporary access to the internal space of the bag for inspection of the stoma area during the service time of the ostomy appliance. Such opening is especially of interest in the first period after a stoma having been made in order
25 to allow an inspection of the newly formed stoma without having to remove the appliance and also for establishing a suitable regime for exchange of appliances for the ostomate in question. The opening may be provided with a closure corresponding to an adhesive coupling normally used for coupling of collection bags to ostomy body side members of two-piece appliances or a conventional
30 coupling ring for coupling of collection bags to ostomy body side members of two-piece appliances and a matching closure such as the closure disclosed in WO 98/38952.

In a SECOND ASPECT the invention relates to a method of applying an ostomy appliance comprising a front wall and a rear wall of flexible material forming a bag, said rear wall having an opening for receiving a stoma, and being provided with an adhesive wafer for securing the appliance to a user's skin, said wafer

5 having a hole being aligned with the opening for receiving the stoma, wherein the opening of the rear wall has an edge being adapted to be secured to a surface of the adhesive wafer facing away from the user in an attachment zone surrounding the hole of the wafer, and wherein a first part of the edge of the opening of the

10 rear wall is permanently secured to the surface of the wafer in a corresponding first part of the attachment zone, and a second, remaining part of the edge of the opening of the bag is prepared for adhesive sealing of the same to the remaining second part of the attachment zone, said method comprising locating the stoma, adapting the size of the hole of the adhesive wafer to the stoma, aligning the

15 stoma and the hole of the adhesive wafer, placing the adhesive wafer on the abdomen of the ostomate with the stoma projecting into the hole of the wafer and sealing the bag by bringing the remaining part of the edge of the bag into adhesive contact with the remaining second part of the attachment zone.

Alternatively the second aspect could relate to a method of applying an ostomy

20 appliance comprising a front wall and a rear wall of flexible material forming a bag, said rear wall having an opening for receiving a stoma, and said rear wall also being provided with an adhesive wafer for securing the appliance to a user's skin, said wafer having a hole being aligned with the opening for receiving the stoma, wherein the opening has an edge being secured to the surface of the

25 adhesive wafer facing away from the user in an attachment zone surrounding the hole of the wafer, wherein a first part of the edge of the opening of the bag is secured to the surface of the wafer in a corresponding first part of the attachment zone, and wherein a second, remaining part of the edge of the opening of the bag is prepared for adhesive sealing of the same to the remaining second part of

30 the attachment zone, said method comprising locating the stoma, adapting the size of the hole of the adhesive wafer to the stoma, aligning the stoma and the hole of the adhesive wafer, placing the adhesive wafer on the abdomen of the

ostomate with the stoma projecting into the hole of the wafer and sealing the bag by bringing the remaining part of the edge of the bag into adhesive contact with the remaining second part of the attachment zone.

- 5 The ostomy appliance according to the second aspect of the present invention may comprise any feature and/or element of the ostomy appliance of the first aspect of the present invention.

10 In a THIRD ASPECT the invention relates to a method of applying an ostomy appliance comprising a front wall and a rear wall of flexible material forming a bag, said rear wall having an opening for receiving a stoma, and being provided with an adhesive wafer for securing the appliance to a user's skin, said wafer having a hole being aligned with the opening for receiving the stoma, wherein the opening of the rear wall has an edge being adapted to be secured to a surface of
 15 the adhesive wafer facing away from the user in an attachment zone surrounding the hole of the wafer, and wherein a first part of the edge of the opening of the rear wall is permanently secured to the surface of the wafer in a corresponding first part of the attachment zone, and a second, remaining part of the edge of the opening of the bag is prepared for adhesive sealing of the same to the remaining
 20 second part of the attachment zone, said method comprising locating the stoma, aligning the stoma and the hole of the adhesive wafer, placing the adhesive wafer on the abdomen of the ostomate with the stoma projecting into the hole of the wafer, locating the sealing member, enlarging the second hole of the sealing member by everting or rolling an inner rim of the second hole adapting the size
 25 and shape of the hole to the stoma, aligning the stoma and the second hole, placing the sealing member on the abdomen of the ostomate with the stoma projecting into the second hole, and bringing the sealing member to seal between the adhesive wafer and the stoma.

- 30 Alternatively the third aspect could relate to a method of applying an ostomy appliance comprising a front wall and a rear wall of flexible material forming a bag, said rear wall having an opening for receiving a stoma, and said rear wall

also being provided with an adhesive wafer for securing the appliance to a user's skin, said wafer having a hole being aligned with the opening for receiving the stoma, said hole comprising a sealing member having a second hole for receiving the stoma, wherein the opening has an edge being secured to the surface of the adhesive wafer facing away from the user in an attachment zone surrounding the hole of the wafer, wherein a first part of the edge of the opening of the bag is secured to the surface of the wafer in a corresponding first part of the attachment zone, and wherein a second, remaining part of the edge of the opening of the bag is prepared for adhesive sealing of the same to the remaining second part of the attachment zone, said method comprising locating the stoma, aligning the stoma and the hole of the adhesive wafer, placing the adhesive wafer on the abdomen of the ostomate with the stoma projecting into the hole of the wafer, locating the sealing member, enlarging the second hole of the sealing member by everting or rolling an inner rim of the second hole adapting the size and shape of the hole to the stoma, aligning the stoma and the second hole and placing the sealing member on the abdomen of the ostomate with the stoma projecting into the second hole, and bringing the sealing member to seal between the adhesive wafer and the stoma.

20 The ostomy appliance according to the third aspect of the present invention may comprise any feature and/or element of the ostomy appliance of the first aspect of the present invention.

25 The adhesive wafer may comprise any skin-friendly adhesive known per se, e.g. an adhesive comprising hydrocolloids or other moisture absorbing constituents for prolonging the time of use forming the surface to be secured to the user's skin. The adhesive may e.g. be of the type disclosed in those disclosed in US patent Nos. 4,367,732, 5,051,259, 5,714,225, 6,171,594, 6,303,700, 6,451,883, or 6,437,038, or in WO Publication Nos. 00/54820, or 01/05340.

30 A sealing member may suitably be made of a material of the kind disclosed in US Patent No. 6,509,391, or 6,332,879. Thus, the elastic and plastic properties may

be selected by the skilled in the art in accordance with the desired properties for the actual purpose, including a self-sealing effect obtainable using a sealing member made from an adhesive material showing absorbing and swelling properties when contacted by aqueous material.

5

A carrier sheet may be present on the surface of the adhesive wafer facing the bag and may any suitable thermoplastic material known per se for use in the preparation of ostomy appliances e.g. a foam, a non-woven layer or a polyurethane, polyethylene, polyester or polyamide suitable for attachment of a collecting bag using an adhesive or by welding.

10

The collection bag may be made in analogy with and from materials conventionally used for the preparation of ostomy appliances. Such materials are suitably films composed of any suitable material, which is heat sealable and sufficiently impervious for unpleasant odours such as polyolefin films or combinations of such films, e.g. polyethylene or a coextrudate of polyethylene and polyvinylidene chloride. Suitably the bag is made from front and rear walls welded in a manner known per se along the rim forming a bag. When cutting or punching the walls, an opening for receiving a stoma is suitably also punched in the wall to form the rear wall.

15

20

A protective cover or release liner may for instance be siliconized paper. It does not need to have the same contour as the dressing, e.g. a number of dressings may be attached to a larger sheet of protective cover. The protective cover is not present during the use of the dressing of the invention and is therefore not an essential part of the invention.

25

Description of the Preferred Embodiments

The invention is now explained more in detail with reference to the drawings showing preferred embodiments of the invention.

30

Reference is made to figure 1 showing an ostomy appliance 1 of the invention in its open state. The ostomy appliance comprises a front wall 2 and a rear wall 3 of

flexible material forming a bag, said rear wall having an opening 4 for receiving a stoma, and said rear wall also being provided with an adhesive wafer 5 for securing the appliance to a user's skin, said wafer having a hole 6 being aligned with the opening for receiving the stoma, wherein the opening has an edge 7,7' being secured to the surface of the adhesive wafer facing away from the user in an attachment zone 8 surrounding the hole of the wafer, wherein a first part of the edge 7 of the bag is secured to the surface of the wafer in a corresponding first part of the attachment zone, and wherein a second, remaining part 7' of the edge of the bag is prepared for adhesive sealing of the same to the remaining second part 8 of the attachment zone. The edge of the opening of the bag is provided with a stiffening element 9.

Fig. 2 shows another embodiment of an ostomy appliance 11 of the invention in its open state applied to a users abdomen. The ostomy appliance comprises a front wall 2 and a rear wall 3 of flexible material forming a bag, said rear wall having an opening 4 for receiving a stoma 12, and said rear wall also being provided with an adhesive wafer 5 for securing the appliance to a user's skin, said wafer having a hole 6 being aligned with the opening for receiving the stoma, wherein the opening has an edge 7,7' being secured to the surface of the adhesive wafer facing away from the user in an attachment zone 8 surrounding the hole of the wafer, wherein a first part of the edge 7 of the bag is secured to the surface of the wafer in a corresponding first part of the attachment zone, and wherein a second, remaining part 7' of the edge of the bag is prepared for adhesive sealing of the same to the remaining second part 8 of the attachment zone. The edge of the opening of the bag is provided with a stiffening element 9. In the hole 6 of the wafer is a separate sealing member 13 sealing against the stoma and the edge of the hole of the wafer.

Fig. 3 shows further embodiment of an ostomy appliance 21 of the invention in its closed state seen from the surface facing away from the user. The ostomy appliance corresponds to the embodiment shown in Fig.1 except that in front wall 2 is provided with an opening provided with cover 14, which may be released and

resealed and thus giving temporary access to the internal space of the bag for inspection of the stoma area during the service time of the ostomy appliance.

5 Figs. 4, 5a and 5b show a stiffening element **31** for use in an ostomy appliance of the invention. The stiffening element is in the form of a circular ring **32** provided with two notches **33** dividing the circular ring into two parts – a first part **34** and a second part **36**. The notches provide predetermined zones in which the stiffening element is readily folded. The notches are in this embodiment placed on the surface to be attached to an adhesive wafer of an ostomy appliance of the
10 invention.

Claims

1. An ostomy appliance comprising a front wall and a rear wall of flexible material forming a bag, said rear wall

5

- having an opening for receiving a stoma, and
- being provided with an adhesive wafer for securing the appliance to a user's skin, said wafer having a hole being aligned with the opening for receiving the stoma,

10

wherein the opening of the rear wall has an edge being adapted to be secured to a surface of the adhesive wafer facing away from the user in an attachment zone surrounding the hole of the wafer, and

15 wherein

- a first part of the edge of the opening of the rear wall is permanently secured to the surface of the wafer in a corresponding first part of the attachment zone, and

20

- a second, remaining part of the edge of the opening of the bag is prepared for adhesive sealing of the same to a remaining second part of the attachment zone.

2. An ostomy appliance according to claim 1, wherein the second, remaining part of the edge of the opening of the bag is prepared for permanently adhesive sealing of the same to the remaining second part of the attachment zone.

25

3. An ostomy appliance as claimed in claim 1 or 2 wherein the ostomy appliance further comprises a separate sealing member disposed in the hole of the wafer surrounding the stoma and having a hole for accommodating the stoma.

30

4. An ostomy appliance as claimed in any of claims 1-3 wherein the second part of the edge of the bag is secured to one surface of a stiffening element.
5. An ostomy appliance as claimed in claim 4 wherein the first and the second part of the edge of the bag are secured to a first and a second part, respectively, of one surface of the stiffening element.
6. An ostomy appliance as claimed in claim 4 or 5 wherein the stiffening element is a flat ring provided with two notches dividing the flat ring into two parts.
7. An ostomy appliance as claimed in claim 6, wherein the notches stretch essentially along a chord of the flat ring.
8. An ostomy appliance as claimed in claim 7, wherein the notches stretch essentially along a diameter of the flat ring.
9. An ostomy appliance as claimed in any of claims 4-8 wherein the part of the stiffening element secured the second part of the bag is provided with an adhesive layer being covered by a protecting layer.
10. An ostomy appliance as claimed in any of claims 4-8 wherein the second part of the attachment zone of the wafer is provided with an adhesive layer being covered by a protecting layer.
11. A method of applying an ostomy appliance according to claim 1, said method comprising
- locating the stoma,
 - adapting the size of the hole of the adhesive wafer to the stoma,
 - aligning the stoma and the hole of the adhesive wafer,
 - placing the adhesive wafer on the abdomen of the ostomate with the stoma projecting into the hole of the wafer and

- sealing the bag by bringing the remaining part of the edge of the bag into adhesive contact with the remaining second part of the attachment zone.

5 12. A method of applying an ostomy appliance according to claim 3, said method comprising

- locating the stoma,
- aligning the stoma and the hole of the adhesive wafer,
- placing the adhesive wafer on the abdomen of the ostomate with the
10 stoma projecting into the hole of the wafer,
- locating the sealing member,
- enlarging the second hole of the sealing member by everting or rolling
 an inner rim of the second hole adapting the size and shape of the
 hole to the stoma,
- 15 - aligning the stoma and the second hole,
- placing the sealing member on the abdomen of the ostomate with the
 stoma projecting into the second hole, and
- bringing the sealing member to seal between the adhesive wafer and
20 the stoma.

Abstract**An Ostomy Appliance**

- 5 An ostomy appliance comprising a front wall and a rear wall of flexible material forming a bag, said rear wall having an opening for receiving a stoma, and said rear wall also being provided with an adhesive wafer for securing the appliance to a user's skin, said wafer having a hole being aligned with the opening for receiving the stoma, wherein the opening has an edge being secured to the
- 10 surface of the adhesive wafer facing away from the user in an attachment zone surrounding the hole of the wafer, wherein a first part of the edge of the opening of the bag is secured to the surface of the wafer in a corresponding first part of the attachment zone, and wherein a second, remaining part of the edge of the
- 15 second part of the attachment zone renders it possible for a nurse to observe the stoma area during adaptation of such a sealing member when applying one-piece appliances.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5a




FIG. 5b

INTERNATIONAL SEARCH REPORT

International Application No

PCT/DK2004/000211

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61F5/445 A61F5/443 A61F5/448

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 429 626 A (FENTON LEONARD) 4 July 1995 (1995-07-04) column 5, line 1 - line 35; figures 3-5 column 3, line 8 - column 4, line 23 -----	1-4,8-12
X	GB 2 017 501 A (MATBURN LTD) 10 October 1979 (1979-10-10) the whole document -----	1,2
X	GB 2 115 291 A (MATBURN) 7 September 1983 (1983-09-07) page 1, line 73 - page 2, line 10; figures ----- -/--	1

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

24 January 2005

Date of mailing of the international search report

23/02/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 opo nl.
Fax: (+31-70) 340-3016

Authorized officer

Germano, A

INTERNATIONAL SEARCH REPORT

International Application No

PCT/DK2004/000211

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98/17212 A (GOTHJAELPSEN LAILA BUSK ;CLOK DANUTA (DK); COLOPLAST AS (DK); SLET) 30 April 1998 (1998-04-30) cited in the application paragraph '0083! - paragraph '0085!; figures 11-18 -----	1,10-12
A	EP 0 259 184 A (COLOPLAST AS) 9 March 1988 (1988-03-09) -----	
A	FR 2 816 202 A (HUET BERNARD) 10 May 2002 (2002-05-10) -----	
A	US 5 051 259 A (OLSEN HANS ET AL) 24 September 1991 (1991-09-24) cited in the application -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/DK2004/000211

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5429626	A	04-07-1995 EP 0672399 A2	20-09-1995
GB 2017501	A	10-10-1979 AU 525363 B2	04-11-1982
		AU 4530979 A	27-09-1979
		CA 1131531 A1	14-09-1982
		DE 2911314 A1	04-10-1979
		DK 119079 A	24-09-1979
		FR 2420337 A1	19-10-1979
		IT 1116004 B	10-02-1986
		JP 54135492 A	20-10-1979
		US 4252120 A	24-02-1981
GB 2115291	A	07-09-1983 AU 1177083 A	01-09-1983
		DK 82683 A	25-08-1983
		ES 270504 Y	16-02-1984
		FR 2523839 A1	30-09-1983
WO 9817212	A	30-04-1998 DK 116696 A	23-04-1998
		AU 721675 B2	13-07-2000
		AU 4616397 A	15-05-1998
		CA 2269575 A1	30-04-1998
		CN 1233945 A	03-11-1999
		WO 9817212 A1	30-04-1998
		EP 0998247 A1	10-05-2000
		JP 2001502570 T	27-02-2001
		NO 991905 A	22-06-1999
		US 2003004477 A1	02-01-2003
		AT 232747 T	15-03-2003
		AU 729075 B2	25-01-2001
		AU 4616297 A	15-05-1998
		CA 2269325 A1	30-04-1998
		CN 1233965 A	03-11-1999
		DE 69719206 D1	27-03-2003
		DE 69719206 T2	13-11-2003
		WO 9817329 A1	30-04-1998
		EP 0938349 A1	01-09-1999
		ES 2189981 T3	16-07-2003
		JP 2001502569 T	27-02-2001
		NO 991904 A	22-06-1999
		US 2002120032 A1	29-08-2002
		AT 219913 T	15-07-2002
		AU 726169 B2	02-11-2000
		AU 7425898 A	30-12-1998
		BR 9809692 A	11-07-2000
		CA 2291035 A1	03-12-1998
		CN 1258208 T	28-06-2000
		DE 69806379 D1	08-08-2002
		DE 69806379 T2	06-03-2003
		DK 68998 A	27-11-1998
		WO 9853771 A1	03-12-1998
		DK 984750 T3	28-10-2002
		EP 0984750 A1	15-03-2000
		ES 2177009 T3	01-12-2002
		JP 2001526576 T	18-12-2001
		NO 995740 A	18-01-2000
		PL 336960 A1	31-07-2000
		US 6332879 B1	25-12-2001
		AU 7426598 A	30-12-1998

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/DK2004/000211

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 9817212	A		WO	9854269 A1	03-12-1998
			EP	0985006 A1	15-03-2000
EP 0259184	A	09-03-1988	DK	422386 A	05-03-1988
			DE	3774806 D1	09-01-1992
			EP	0259184 A1	09-03-1988
			ES	2028092 T3	01-07-1992
			US	4826495 A	02-05-1989
FR 2816202	A	10-05-2002	FR	2816202 A1	10-05-2002
US 5051259	A	24-09-1991	DK	657187 A	16-06-1989
			AT	80992 T	15-10-1992
			AU	608408 B2	28-03-1991
			AU	2905089 A	19-07-1989
			CA	1323270 C	19-10-1993
			DE	3875112 D1	05-11-1992
			DE	3875112 T2	15-04-1993
			WO	8905619 A1	29-06-1989
			EP	0345331 A1	13-12-1989
			ES	2009459 A6	16-09-1989
			IE	61425 B1	02-11-1994
			JP	2502884 T	13-09-1990
			JP	2752207 B2	18-05-1998
			RU	2060035 C1	20-05-1996